



1D CCD barcode scanner

Features

- Built-in CCD Engine
- Quicker scan rate: smart detection, up to 300 scans/sec
- Multi - selection for different usage.
- Multi-interfaces just by change cable.
- Suitable for Supermarket, POS (Point-of-sales), inventory management or Document tracking.



Scanners Specifications :

Model Name	CR6307A	CR6327A
Description	Handheld	Auto-sensing (Up to 180 mm)
Engine	RIOTEC 1D engine	

Performance Characteristics

• Light Source	610nm~640nm Red LED
• Depth of field	13 mil EAN 13 : 420 mm max
• Scan Rate	300 scans/sec
• Best Resolution	4 mil Code 39
• Print Contrast	30% or more
• Indicators	LED & beeper
• Interface	USB HID , USB Serial (by request) , RS232 (by request)
• Symbolologies	Code 128,EAN-13, EAN-8,, Code 39, UPC-A, UPC-E,Codabar,Interleaved 2 of 5, ISSN, ISBN,Code 93,MSI,Matrix 2 of 5,Industrial 2 of 5,Code 11,RSS-14 RSS-14-limited,RSS-14-expand

Electrical Characteristics

• Input voltage	5 VDC \pm 5%
• Current - operating	60mA max

Physical Characteristics

• Dimension (L x W x H)	90 x 65 x 160 mm
• Weight	110 g +/- 5 g (No cable)

User Environment

• Temperature-operation	0°C to 50°C
• Temperature-storage	-10°C to 60°C
• Humidity	Up to 95% relative humidity, non-condensing
• Ambient Light	100,000 lux max

Depth of Field (DOF is measured at the office under 600 lux and by Standard barcode. There are +/- 10 mm Torrence. DOF may be also impacted by barcode quality and environmental conditions.)

• 4 mil Code39	55mm ~ 160mm
• 5 mil Code39	50mm ~ 180mm
• 13 mil EAN 13	35mm ~ 420mm

Product specification is subject to change without notice.

RIOTEC CO., LTD.

8F., 196-2, DaTong Rd., Sec. 3, Xizhi Dist., New Taipei City 221, Taiwan

TEL : +886-2-8647-1828

FAX : +886-2-8647-1800

E-mail : sales@riotec.com.tw

Web : www.riotec.com.tw