



## ANDROSCAN mobile barcode scanner

### Features

ANDROSCAN = mini barcode scanner + Scan Holder

\*\* With ANDROSCAN, it can make Android OTG smartphone become data collector. Plug and Play.

\*\* Mini barcode scanner is with touch trigger. The operation is easy.

\*\* Scan Holder can be used for different size of Android OTG devices. (from 4" to 6" size)

\*\* ANDROSCAN has metal clip which can fix smartphone with ANDROSCAN easily.

\*\* Scan holder solves the issue for micro USB port in the bottom of phone.

\*\* Scan holder H92PH can provide power to mini barcode scanner.

\*\* You don't need to remove Scan holder when in charge. You can charge the battery inside & smart-phone battery both through its micro USB port.

\*\* Scan Holder has "Cable Storage Area" which stores redundant cable here.



### Specifications :

Model Name		DC9250KPH	DC9250KNH
Engine		2D engine	
Performance Characteristics			
• Illumination Element	White LED		
• Aiming LED	Red Light : 625nm ± 3nm		
• Depth of field	13mil EAN13: 210 mm		
• Best resolution	4mil Code39		
• Sensor	CMOS (640x480 pixels)		
• Scan Angle	Roll: 360 ° Pitch: 50 ° Skew : 50°		
• Charge	Micro USB port		
• Interface	USB HID, USB Serial <by request>		
• Cable supported	Micro USB cable or Type-C cable		
• Print contrast	≥ 30%		
• Symbolologies	1D: EAN-8 , EAN-13 , UPC-A , UPC-E , Code 39 , Code 93 , Code 128 Codabar , Interleave 2 of 5 , MSI , GS1 Databar , ISBN , GS1-128 2D: PDF417 , QR Code , DataMatrix , Aztec		
• Scan Holder	with H92P (with battery) rechargeable Li-Ion 3.7V 900mAH	with H92N (without battery)	
Electrical Characteristics			
• Input voltage	5 V/DC ± 5%		
• Current - operating	390 mA		
Physical Characteristics			
• Dimension (L x W x H)	142 x 75.2 x 46 mm		
• Color of housing	Black		
• Weight	134 g+/- 5 g	112g+/- 5 g	
Environment			
• Temperature-operation	0°C to 50°C		
• Temperature-storage	-10°C to 60°C		
• Humidity-operation	5% to 95% relative humidity, non-condensing		
Decode Zone(Based on Symbol's Standard Code 39 PCS=0.9 label and 600 lux environment. There are +/- 1 cm tolerance)			
• 4 mil Code 39	50mm ~ 115mm		
• 5 mil Code 39	50mm ~ 145mm		
• 13 mil EAN-13	60mm ~ 210mm		

Product specification is subject to change without notice.

RIOTEC CO., LTD.

8F., 196-2, DaTong Rd., Sec. 3, Xizhi Dist., New Taipei City 221, Taiwan

TEL : +886-2-8647-1828

FAX : +886-2-8647-1800

E-mail : sales@riotec.com.tw

Web : www.riotec.com.tw